

**COVENTRY
SCALE
COMPANY**



GEX_XL

"GEX-FZ-1G": High precision floor balance, for ATEX zone 0

High precision floor balance for hazardous areas.
Protection rating II 1G Ex ia II B T4 Ga for gas.
CE-M approved (OIML R-76 / EN 45501).

CAPACITY (kg): 300.



**The best solution
for advanced industrial
applications**

MAIN FEATURES

- 27-key numeric and functional waterproof keyboard.
- 9-digit 25 mm LCD display.
- IP65 stainless steel structure.
- Dimensions 800 x 600 x 142 mm.
- Weighing sensor with tuning fork technology.
- Stainless steel plate, dimensions 800 x 600 mm;
- 100 – 240VAC power supply unit in safe area, with RS232 serial port.
- 5 m cable between power supply and weight indicator.
- 5 m cable between platform and weight indicator.
- 2.5 m power cable.
- Operating temperature +5°C...+40°C (display and platform, 0°C...+40°C (power supply), non-condensing relative humidity 85%.
- Version approved for CE-M II legal-for-trade use.

AVAILABLE FUNCTIONS

- Zeroing;
- Semiautomatic tare;
- Preset tare;
- Tolerance check;
- Totalization in loading and unloading.
- Up to 100 storable tares;
- Bar graph display in relation to flow rate;
- 6 configurable serial communication protocols, sending the string continuously, at stability, on demand or at the press of a key;
- 5 selectable weighing filters;
- Zero tracking.

WEIGHING MODES

- Weighing in grams;
- Percentage weighing for formulation and recipe dosing;
- Customized coefficient for liquid weighing and grammage.

MAIN CERTIFICATIONS

- II 1G Ex ia II B T4 Ga
- OIML R76

Manuals, safety instructions and ATEX EU declaration of conformity in English language.

DETAIL 1



DETAIL 2



VERSIONS

Available versions

Codice	Classe	Piatto Max (mm)	Max (kg)	d (g)	M (g)*	Linearità (g) +/-	Ripetibilità (g)
GEX-FZ300K-1G	II	800 x 600	300	1	10	5	8

**COVENTRY
SCALE
COMPANY**



COVENTRY SCALE COMPANY LTD
UNIT 8, SPITFIRE CLOSE - CV5 6UR - COVENTRY
Tel. 0044-2476-593500
Fax. 044-2476-601239
E-mail info@coventryscale.co.uk
Web www.coventryscale.co.uk