

T-C6

"T - C6" SERIES - SINGLE CELL PLATFORMS



Small and medium capacity electronic platforms with a AISI304 stainless steel surface.

- Up to 30000d resolution.
- OIML R60 C6.
- IP65

### **MAIN FEATURES**

- Functions with a C6 6000e approved aluminium "single point" load cell according to OIML R60 standards with protection against dust and water splashes according to IP65 standards (350 Ohm input resistance).
- Steel tubular structure, oven-fire painted blue, with adjustable resting feet and level.
- Fitted with AISI 304 satin finish stainless steel loading surface.
- Up to 15 Vdc power supply.
- Shielded 3m connection cable with connectors for connection to the indicator.
- Special sizes and capacities (upon estimate).


### **OPTIONS FOR ATEX VERSION**

- CCATEX: ATEX certificate for each load cell
- DCATEX2GD: Declaration of ATEX conformity of whole PLATFORM + ATEX 2GD DINI ARGEO INDICATOR
- DCATEX3GD: Declaration of ATEX conformity of whole PLATFORM + ATEX 3GD DINI ARGEO INDICATOR

### SUPPORT BRACKETS AND COLUMNS

• Example of use with bracket, attached column or floor column.





# **AVAILABLE UPON PRICE ESTIMATE**

- Belt and roller units to be applied on the loading Surface.
- Special sizes and capacities.

## **VERSIONS**

Available versions						
Codice	l x w x h (mm)	Max (kg)	d (g)	<b>M</b> (g)*	<b>M</b> 2R (g)*	d HR (g)*
TS3C6	230x330x93	3	0,5	0,5		0,1
TS6C6	230x330x93	6	1	1	0,5/1	0,2
TS12C6	230x330x93	12	2	2	1/2	0,5
TT6C6	330x330x93	6	1	1	0,5/1	0,2
TT12C6	330x330x93	12	2	2	1/2	0,5
TT30C6	330x330x93	30	5	5	2/5	1
TQ30C6	400x400x115	30	5	5	2/5	1
TQ60C6	400x400x115	60	10	10	5/10	2

<sup>(\*)</sup> Divisions obtainable only with the relative options, in combination with Dini Argeo weight indicator.



COVENTRY SCALE COMPANY LTD
UNIT 8, SPITFIRE CLOSE - CV5 6UR - COVENTRY

Tel. 0044-2476-593500 Fax. 044-2476-601239 E-mail info@coventryscale.co.uk

Web www.coventryscale.co.uk